



Geberit Monolith Plus sanitary module for wall-hung WC, 114 cm







Example image

Application purposes

- · For renovations, conversions and new buildings
- For wall inlets with inlet height > 23 cm
- For replacing low-level exposed cisterns
- · For replacing half-high level exposed cisterns
- · For replacing wall-hung WCs with close-coupled exposed cistern
- · For replacing wall-hung WCs with pressure flushing valve
- For replacing wall-hung WCs with concealed cistern with maximum service opening height < 109 cm
- · For Geberit AquaClean WC complete solutions
- For connecting Geberit AquaClean WC enhancement solutions, with accessories
- For mounting on finished floors
- · For installation in front of drywalls or solid walls
- For compensating the offset between WC connections and wall drains using a stepped straight connector for wall-hung WCs

Characteristics

- Dual flush
- · Compensation of dimensional tolerances possible
- Height-adjustable up to 7 cm
- Fastening height WC ceramic appliance 35 ± 1 cm
- · Cistern, fully insulated against condensation
- · Side cladding made of aluminium brushed
- Self-supporting
- Soft-touch buttons for flush actuation and odour extraction
- Orientation light and odour extraction activated when a user approaches
- · Orientation light can be set in seven colours
- Day/night detection can be set for orientation light
- Odour extraction unit with ceramic honeycomb filter can be installed without tools
- Odour extraction unit automatically switches off after a predefined running time
- Operation with extra-low voltage, no mains voltage in cistern
- Water supply connection on the rear centre
- Water supply connection on the left/right possible with accessories

· Water supply connection on the bottom

Technical data

| Protection degree | IPX4 |
|--|--------------|
| Protection class | 1 |
| Nominal voltage | 100-240 V AC |
| Mains frequency | 50-60 Hz |
| Operating voltage | 4.1 V DC |
| Power consumption | 5 W |
| Flow pressure | 0.1-10 bar |
| Flow pressure | 10-1000 kPa |
| Maximum operating temperature, water | 25 ℃ |
| Flush volume | 61 |
| Flush volume small | 31 |
| Calculated flow rate | 0.11 l/s |
| Minimum flow pressure for calculated flow rate | 0.5 bar |
| Minimum flow pressure for calculated flow rate | 50 kPa |

Scope of delivery

- Water supply connection set with 2 angle stop valves, 1/2"
- Flush bend extension 160 mm
- Sleeve made of EPDM, ø 44 / 55 mm
- · Straight connector made of PE-HD, ø 90 mm
- Adapter socket made of PE-HD, ø 90 / 110 mm
- 2 threaded rods M12
- Sound insulation set
- · Female socket for mains connection
- Power supply unit
- · Base cover
- Fastening material for drywall
- Fastening material
- · Fastening material for installation in front of concealed cisterns

| Art. no. | Colour / surface | В | Н | T |
|--------------|---|---------|--------|---------|
| 131.231.SJ.5 | Front cladding: black glass Side cladding: aluminium | 50.5 cm | 114 cm | 10.6 cm |

Accessories

- Geberit straight connector set for wall-hung WC, stepped by 3 cm
- Geberit straight connector set for wall-hung WC, stepped by 7 cm
- Geberit outlet mounting box
- · Lateral water supply connection set for Geberit Monolith sanitary module for WC



- The colour and structure of natural products may vary
- Sanitary modules with slate look (.00) or concrete look (.JV) are intended exclusively for use with the items under "Can be combined with".