



-

Mirage - Top Flush Suite

SUITE-MIRAGE TF-WHI

CISTERN-MIRAGE/IQWA TF-WHI PANS-MIRAGE-** SEAT-MIRAGE **(WOOD) MECH-UNIVERSAL DUAL FLUSH (WIRQ) FIX-PAN FIXATION KIT (L BRACKET) SEREX


CLOSE COUPLE, OPEN RIM, TOP FLUSH


WEIGHT OF PAN:	28,3 kg
WEIGHT OF CISTERN:	12.3 kg
CISTERN WATER CAPACITY:	10 Lt
PAN FLUSH VOLUME:	3/6 Lt
PAN WIDTH:	365 mm
PAN HEIGHT:	400 mm
CISTERN WIDTH:	395 mm
CISTERN HEIGHT:	382 mm
COMBINED HEIGHT:	825 mm
INSTALLED MAX LENGTH:	665 mm

The Mirage is a top flush suite.

MIRAGE SUITE INSTALLATION GUIDE:

- 1. Fit inlet valve and flushing mechanism, as per manufacturer's instructions.
- 2. Attach cistern to pan using fixation bolts.
- 3. Fit seat, use the manufacturer's instructions.
- 4. Place the pan with cistern on flat (even) surface for best results.
- 5. Make markings on floor surface, for drilling of fixation holes (pan).
- 6. Remove pan and cistern, drill holes into concrete floor.
- 7. Slide outlet of pan onto bung of outlet pipe fitted by a qualified plumber.
- 8. Attach pan to floor using screw fixations.
- 9. Connect to the water supply.







AVAILABLE COLOURS:





